



Construction Industry Authority of the Philippines
REQUEST FOR QUOTATION/PROPOSAL

CIAP-F-PrM-03
Rev. No.: 00

Procurement of Various ICT Office Equipment for Official Use of CIAP.

P.R. No./Date: **25-05081, 25-05082, 25-05083 | 30 May 2025**

RFQ/P No. / Date: **2025-06-062 | 02 June 2025**

The Construction Industry Authority of the Philippines (CIAP) invites all eligible suppliers, contractors and consultants to quote the best offer for the described item/s in the attached **Terms of Reference/Technical Specifications** subject to the Terms and Conditions and within the **Approved Budget for the Contract (ABC)**.

The following are the required document/s to be submitted as attachment/s to the quotation/proposal:

(Please submit the documents required to be submitted by the bidder pursuant to Annex "H"-Appendix A of Revised of The 2016 Revised IRR)

- 1 **Mayor's/Business Permit**
- 2 **PhilGEPS Registration Number**
- 3 **BIR Certificate of Registration (BIR Form No. 2303)**
- 4 **Signed Terms of Reference or Technical Specifications, if applicable**

This pro-forma quotation maybe submitted through registered or electronic mail to the CIAP Bids and Awards Committee Secretariat at address indicated below or email to bac_ciap@construction.gov.ph/johnvincentpeduche@construction.gov.ph on or before 10 June 2025, 05:00 PM, together with any additional requirements indicated in the attached Terms of Reference / Technical Specifications, and subject to the following Terms and Conditions:

1. All entries shall be typed or written in a clear legible manner.
2. No alternate quotation/offer is allowed, suppliers who submitted more than one quotation shall be automatically disqualified.
3. All prices offered herein are valid, binding and effective for **sixty (60)** calendar days upon receipt of the bid. Alternative bids shall be rejected.
4. Price quotations to be denominated in Philippine Peso shall include all applicable government taxes subject to **(BIR 2306) 5% R-VAT and (BIR 2307) 1% (PO) or 2% (JO) deductions.**
5. CIAP-BAC Technical Working Group may require you to submit documents that will prove your legal, financial and technical capability to undertake this contract.
6. Salient provisions of the IRR of RA 9184: Section 68 - Liquidated Damages and Section 69 - Imposition of Administrative Penalties shall be observed.
7. CIAP reserves the right to reject any and all quotations, declare a failure, or not award the contract pursuant to Sec 41 of the same IRR.
8. In case of tie quotations, suppliers' presence is required during tie breaking through draw lots or toss coin.
9. In case supplier pro forma quotation is submitted, conditions will be governed by the submitted signed **Terms of Reference/Technical Specifications**.
10. Payment shall be made through **check payment (Landbank)**.
11. For bidders with Landbank of the Philippines Bank Account Number, please write Account Number: _____.

Very truly yours,
(ORIGINAL Copy Signed)

John Vincent B. Peduche

Secretariat, Bids and Awards Committee

CONSTRUCTION INDUSTRY AUTHORITY OF THE PHILIPPINES

4th Floor Room 410, Executive Building Center, 369 Sen. Gil Puyat Ave., cor. Makati Ave., Makati City

Telephone: 0917-855-7198 | e-mail: bac_ciap@construction.gov.ph

Item	QTY	ABC	Technical Specifications	Brand/Model	Unit Price	Total Amount
				(To be filled-out by the supplier)		
1	2 pcs.	₱ 170,000.00	Rackmount Uninterruptible Power Supply with Railkit ** See attached for complete Technical Specifications **			
2	40 pcs.	₱ 240,000.00	Desktop Uninterruptible Power Supply ** See attached for complete Technical Specifications **			
3	6 pcs.	₱ 108,000.00	28-port Gigabit Smart Managed Switch with 4-port Gigabit Combo Uplinks ** See attached for complete Technical Specifications **			
4	6 pcs.	₱ 348,000.00	52-port Gigabit Smart Managed Switch with 4-port Gigabit 10G Uplinks ** See attached for complete Technical Specifications **			
Total ABC		₱ 866,000.00				
Delivery and Other Instructions:			Within 30-45 days upon receiving of NOA/PO.			

(Please provide **complete** information below)

We undertake, if our Proposal is accepted, to supply/deliver the goods in accordance with the specifications and/or delivery schedule.

We agree to abide by this proposal for the price validity period specified in the terms and conditions and it shall remain binding upon us and may be accepted at any time before the expiration of that period.

Until a Purchase/Job Order or a Contract is prepared and executed, this Quotation/Proposal shall be binding upon us. We understand that CIAP is not bound to accept the lowest or any proposal that CIAP may receive.

Signature over Printed Name : _____

Designation/Position : _____

Name of Company : _____

Address : _____

Telephone / Fax : _____

E-mail Address : _____


Company Tax Identification Number : _____

TECHNICAL SPECIFICATIONS


Purchase Request of Rackmount Uninterruptible power supply (UPS) with railkit				
Qty.	Unit	Description / Minimum Specification	Est. Cost / Unit	Amount
2	Pcs	<p>Rackmount Uninterruptible power supply (UPS) with Railkit</p> <p><u>Specifications:</u></p> <ul style="list-style-type: none"> • Main Input Voltage: 230 V • Product or component type: Uninterruptible power supply (UPS) • Other Input Voltage: 220 V, 240 V • Main Output Voltage: 230 V • Other Output Voltage: 220 V, 240 V • Rated power in W: 2700 W • rated power in VA: 3000 VA • Number of rack unit: 2U • Cable length: 1.5 m • Number of cables: 1 • Provided equipment: 1 IEC 60320 C19 to Schuko power cable, 1 IEC 60320 C13 to C14 power cable, 1 USB cable, 1 RS-232 configuration cable, 1 rack mounting brackets, 1 rack mounting support rails, user manual • Range of product: Easy UPS On-Line • Battery type: Lead-acid battery • Battery voltage: 72 V • Extended runtime: 0 • Number of battery filled slots: 0 • Number of battery free slots: 0 • Battery recharge time: 4 h • Battery life: 3...5 year(s) • Replacement battery: Yes • Battery charger power: 60 W rated • Max runtime: 3 min • Number of power module filled slots: 0 • Number of power module free slots: 0 • Redundant: No • Colour: Black (RAL 7010) • Height: 8.6 cm • Width: 43.8 cm • Depth: 63.2 cm • Net weight: 28.5 kg • Mounting location: Front • Mounting preference: Lower • Mounting mode: Rack-mounted • USB compatible: Yes • Mounting position: Horizontal • Input voltage limits: 110...285 V 40% load, 180...285 V full load • Network frequency: 40...70 Hz auto sensing • Maximum configurable power in VA: 3000 VA • Maximum configurable power in W: 2700 W • Output frequency: 50/60 Hz +/- 3 Hz sync to mains • Harmonic distortion: 3 % 	₱ 85,000.00	₱ 170,000.00

	<ul style="list-style-type: none">• UPS type: Double conversion online• Efficiency: 88 % (full load)• Additional information: Configurable for 220 : 230 or 240 nominal output voltage• Bypass type: Internal bypass (automatic and manual)	
WARRANTY	2 Years warranty or replace	
DELIVERY	Within 30-45 days upon receiving Notice of Award or Purchase Order	

Prepared By:


MIKE KENNETH C. CABUSLAY
Computer Maintenance Technologist I,
PPCMD

Approved By:


ATTY. NATALIE P. LABANG
Division Chief, PPCMD

Reviewed by (for ICT Task Force):


CHARLIE A. BARINQUE
Information Technology Officer
ICT Task Force Member, PPCMD

CONFORME:

This is to certify that the undersigned, as an authorized representative of the Contractor, confirms and complies with all the requirements and deliverables needed for the _____

Name and Signature of Authorized Representative of the Contractor

PhilGEPS Registration Number

Tax Identification Number

Date

TECHNICAL SPECIFICATIONS

Purchase Request of Desktop Uninterruptible power supply (UPS)				
Qty.	Unit	Description / Minimum Specification	Est. Cost / Unit	Amount
40	Pcs	Desktop Uninterruptible power supply (UPS) <u>Specifications:</u> <ul style="list-style-type: none"> • Main Input Voltage: 230 V • Main Output Voltage: 230 V • Rated power in W: 600 W • rated power in VA: 1000 VA • Product or component type: Uninterruptible power supply (UPS) • Input Connection Type: NEMA 5-15P • output connection type: 4 universal receptacle • Cable length: 1.20 m • Number of cables: 1 • Battery type: Lead-acid battery • Provided equipment: User manual • Range of product: Easy UPS On-Line • Number of battery filled slots: 0 • Number of battery free slots: 0 • Battery recharge time: 8 h • Battery voltage: 12 V • Battery Capacity: 9.0Ah • Battery life: 3...5 year(s) • Replacement battery: RBC17 • Extended Runtime: 0 • Number of power module filled slots: 0 • Number of power module free slots: 0 • Redundant: No • UPS size: WS • Colour: Black • Height: 9.25 cm • Width: 16.05 cm • Depth: 30.5 cm • Net weight: 5.7 kg • Mounting preference: No Preference • Mounting mode: Not Rack-mounted • Two post mountable: 0 • USB compatible: No • Network frequency: 50/60 Hz +/- 5 Hz auto-sensing • Input voltage limits: 170...280 V • Maximum configurable power in W: 600 W • Output frequency: 50/60 Hz +/- 1 Hz unsynchronised • UPS type: Line interactive • Wave type: Stepped approximation to a sinewave • Graph display: 1 • Maximum configurable power in VA: 1000 VA • Transfer time: 6 ms typical : 10 ms maximum <ul style="list-style-type: none"> • Product certifications: CE • Standards: EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 • Ambient air temperature for operation: 0...40 °C • Relative humidity: 0...90 % • Operating altitude: 0...6667 ft • Ambient air temperature for storage: -20...50 °C • Storage Relative Humidity: 0...90 % • Storage altitude: 0.0000000000...15240.0000000000 m • Acoustic level: 40 dBA 	₱ 6,000.00	₱ 240,000.00

	<ul style="list-style-type: none"> • IP degree of protection: IP20 • Alarm: Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm • Surge energy rate: 156 • Unit Type of Package 1: PCE • Number of Units in Package 1: 1 • Package 1 Height: 23.7 cm • Package 1 Width: 37.3 cm • Package 1 Length: 14.3 cm • Package 1 Weight: 6 kg • SCC14: 10731304338250 		
WARRANTY	2 Years warranty or replace		
DELIVERY	Within 30-60 days upon receiving Notice of Award or Purchase Order		


Prepared By:


MIKE KENNETH C. CABUSLAY
 Computer Maintenance Technologist I,
 PPCMD

Approved By:


ATTY. NATALIE F. LABANG
 Division Chief, PPCMD

Reviewed by (for ICT Task Force):


CHARLIE A. BARINQUE
 Information Technology Officer
 ICT Task Force Member, PPCMD

CONFORME:

This is to certify that the undersigned, as an authorized representative of the Contractor, confirms and complies with all the requirements and deliverables needed for the _____

 Name and Signature of Authorized Representative of the Contractor

 PhilGEPS Registration Number

 Tax Identification Number

 Date

TECHNICAL SPECIFICATIONS

Purchase Request of Port Gigabit Smart Managed Switch				
Qty.	Unit	Description / Minimum Specification	Est. Cost / Unit	Amount
6	Pcs	28-port Gigabit Smart Managed Switch with 4-port Gigabit Combo Uplinks <u>Specifications:</u> Interface: 24 x 10/100/1000BASE-T ports 4 x Gigabit RJ45/SFP Combo ports Advanced L2 switching and security features L2+ Static Routing Optional "standard mode" or "surveillance mode" management user interface Security: Access Control List Port Security ARP Spoofing Prevention Smart IP-MAC-Port Binding DHCP Server Screening Management: IPv4/ IPv6 Dual Stack Web GUI (supports 10 languages) SmartConsole utility SNMP and RMON Simplified CLI through Telnet QoS: Supports IEEE 802.1p QoS Supports DSCP Advanced Features: Auto Surveillance VLAN Auto Voice VLAN Port or VLAN-based Loopback Detection Cable Diagnostics LLDP/LLDP-MED Number of Ports: 24 10/100/1000 Mbps 4 SFP Port Standard & Functions: IEEE 802.3 10BASE-T Ethernet IEEE 802.3u 100BASE-TX (Fast Ethernet) IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) IEEE 802.3x Flow Control for Full-Duplex Mode Auto-negotiation Network Cables: UTP Cat. 5, Cat. 5e (100 m max.) EIA/TIA-568 100-ohm STP (100 m max.) Full/Half Duplex: Full/half duplex for 10/100 Mbps speeds Full duplex for Gigabit speed AC Input: 100 to 240 VAC 50/60 Hz internal universal power supply Dimensions (W x D x H): 17.32 x 8.27 x 1.73 inches (440 x 210 x 44 mm) 19" standard rack mounting width, 1U height Weight: 5.69 lbs (2.58 kg) Diagnostic LEDs: Power (per device)	₱ 18,000.00	₱ 108,000.00

		Link/Activity/Speed (per 10/100/1000 Mbps port) Link/Activity/Speed (per SFP port) Fan (per device)		
		Inclusion: Mounting Switch Brackets and Nuts Compatibility: Compatible with Fortinet and other Firewall/Switch Equipment		
6	Pcs	52-port Gigabit Smart Managed Switch with 4-port 10G Uplinks Specifications: <ul style="list-style-type: none"> • 48 x 10/100/1000BASE-T PoE ports • 4 x Gigabit GbE/SFP combo ports • Advanced L2 switching and security features • L2+ Static Routing • Optional "standard mode" or "surveillance mode" management user interface • 370W PoE budget 	₱ 58,000.00	₱ 348,000.00
WARRANTY		At least with 3 Years warranty		
DELIVERY		Within 30-45 days upon receiving Notice of Award or Purchase Order		

Prepared By:

Approved By:


MIKE KENNETH C. CABUSLAY
 Computer Maintenance Technologist I,
 PPCMD


ATTY. NATALIE P. LABANG
 Division Chief, PPCMD

Reviewed by (for ICT Task Force):


CHARLIE A. BARINQUE
 Information Technology Officer
 ICT Task Force Member, PPCMD

CONFORME:

This is to certify that the undersigned, as an authorized representative of the Contractor, confirms and complies with all the requirements and deliverables needed for the _____

 Name and Signature of Authorized Representative of the Contractor

 PhilGEPS Registration Number

 Tax Identification Number

 Date